


Di-QSLD1E0

- Graphic LCD display
- Modbus Interface
- Wireless communication
- Quick setup
- Additional options available

DiOne can be humidity, temperature, barometric pressure, differential pressure, carbon dioxide (CO2), volatile organic compounds (VOC), particulate matter (PM) and/or Analog signal transmitters (it depends on the model). Settings of the device (LCD display configuration, Modbus parameters, etc.) can be modified through USB programming unit, PC software or Modbus interface




(1) – RS-485 interface (Modbus RTU) or Industrial Ethernet (Modbus TCP)
(2) – wireless interface (Radio 868 MHz)

DiOne transmitters offer Fieldbus (RS-485 – Modbus RTU) or Industrial Ethernet (Modbus TCP) interfaces for communication with a master device (e.g. PLC, HMI or PC). DiOne transmitters with radio modules (wireless transmission in the 868 MHz frequency band) are also available. DiOne devices may be used in HVAC systems, BMS systems and air parameters monitoring systems (with dedicated ADAPS or IDAPS software).

Technical drawing

© 2023 APONE apone.eu



All dimension in mm. This drawing is for informational purposes only. The manufacturer reserves the right to make changes in the product dimensions without prior notice.

Kod produktu	
Typ urządzenia	Transmitter
Mierzone parametry	Humidity, Temperature, VOC
Zakres pomiarowy	-20…+60 °C, 0…100 %RH, 0…500 VOC index, VOC index 0…500, 0…500 VOC index
Dokładność (maks.)	±0.2 °C, ±15 VOC index, ±2.0 %RH, VOC index ±15, ±15 VOC index
Częstotliwość pomiaru	1 Hz, 1 Hz (humidity), 1 Hz (VOCs)
Typ sensora	Integrated
Filtr sensora	Polyethylene filter (40 µm)
Zasilanie	11.5…27 VDC
Interfejs	Ethernet LAN (Modbus TCP)
Wyjścia analogowe	–
Wyjścia analogowe - typ	–
Wyjścia analogowe - rozdzielczość	–
Wyjścia binarne	–
Wyjścia binarne - parametry	–
Przyłącze elektryczne	Spring connector – 14…20 AWG (2,08…0,516 mm²)
Diody serwisowe	2x LED
Wyświetlacz	LCD (graficzny)
Parametryzacja	Configuration software, Modbus
Stopień ochrony	IP20
Temperatura pracy	0…+50 °C
Wilgotność pracy	0…95 %RH (WITHOUT CONDENSATION)
Typ obudowy	Wall
Materiał obudowy	ABS, Stainless steel
Wymiary obudowy	See: drawing
W komplecie	Manual

Producent zastrzega sobie prawo do dokonywania zmian niektórych parametrów w związku z ciągłą pracą nad udoskonalaniem konstrukcji urządzenia, bez powiadamiania o tym jego użytkowników.

© 2023 APONE apone.eu