


# Li-S00WEE0

- Powerful Microprocessor
- Industrial Ethernet Interface (Modbus TCP)
- Internal and/or External Sensors
- High Accuracy
- Psychometric Calculation (Li-S00... and Li-H00...)
- Additional options available

LiOne can be humidity and/or temperature transmitters (it depends on model). The LiOne line combined with an internal or external sensors provide state-of-the-art functionality. Various models are available including wall, cable or remote sensors. Settings of the device can be modified through PC software.





( 1 ) – Industrial Ethernet (Modbus TCP)

LiOne transmitters offers Industrial Ethernet (Modbus TCP) interfaces. It is the simplest industrial humidity and/or transmitters with Industrial Ethernet interface in APONE's portfolio.

## Technical drawing


© 2023 APONE apone.eu





All dimension in mm. This drawing is for informational purposes only. The manufacturer reserves the right to make changes in the product dimensions without prior notice.


© 2023 APONE apone.eu

| | |
|---|---|
| **Kod produktu** | Li-S00WEE0 |
| **Typ urządzenia** | Transmitter |
| **Mierzone parametry** | Humidity, Temperature |
| **Zakres pomiarowy** | -20...+60 °C, 0...100 %RH |
| **Dokładność (maks.)** | ±0.2 °C, ±2.0 %RH |
| **Częstotliwość pomiaru** | 1 Hz, 1 Hz (humidity) |
| **Dodatkowe opcje** | Psychometric calculations |
| **Typ sensora** | Integrated |
| **Filtr sensora** | Plastic filter, gap dimensions -1.5 x 1.2 mm |
| **Zasilanie** | 8...27 VDC |
| **Interfejs** | Ethernet LAN (Modbus TCP) |
| **Wyjścia analogowe** | – |
| **Wyjścia analogowe - typ** | – |
| **Wyjścia analogowe - rozdzielczość** | – |
| **Wyjścia binarne** | – |
| **Wyjścia binarne - parametry** | – |
| **Przyłącze elektryczne** | DC-JACK connector, RJ-45 Ethernet port |
| **Diody serwisowe** | – |
| **Wyświetlacz** | – |
| **Pamięć - rejestrowane dane** | – |
| **Pamięć - typ** | – |
| **Pamięć - pojemność** | – |
| **Pamięć - częstotliwość zapisu** | – |
| **Parametryzacja** | Configuration software, Ethernet LAN, Modbus |
| **Stopień ochrony** | IP40 |
| **Temperatura pracy** | 0...+60 °C |
| **Wilgotność pracy** | 0...95 %RH (WITHOUT CONDENSATION) |
| **Typ obudowy** | Wall |
| **Materiał obudowy** | Stainless steel |
| **Wymiary obudowy** | See: drawing |
| **W komplecie** | – |

## Produkty powiązane


© 2023 APONE apone.eu



Zasilacz ZAS-24-DIN



Zasilacz ZAS-12-WT



Zasilacz ZAS-12-DIN



Zasilacz ZAS-24-WT

Producent zastrzega sobie prawo do dokonywania zmian niektórych parametrów w związku z ciągłą pracą nad udoskonalaniem konstrukcji urządzenia, bez powiadamiania o tym jego użytkowników.


© 2023 APONE apone.eu