


# Si-U00L1A3

- Powerful Microprocessor
- Functionally Programmable
- Fast Configurations
- Modbus Interface
- Wide range of supply voltage
- Additional options available

SiOne can be humidity, temperature, barometric pressure, differentia pressure, carbon dioxide (CO2), volatile organic compounds (VOC), particulate matter (PM) and/or Analog signal transmitters (it depends on model). The SiOne line combined with an internal and/or external sensors provide state-of-the-art functionality. Various models are available including wall, duct or remote sensors. SiOne is introducing powerful programming capabilities. Settings of the device can be modified through USB programming unit, PC software or Modbus interface. Modbus RTU baud rate, Modbus RTU address and type of Analog outputs can be fast changed by configuration jumpers.





( 1 ) – RS-485 interface (Modbus RTU) or Industrial Ethernet (Modbus TCP)
( 2 ) – programmable relay output On/Off (option)
( 3 ) – programmable (up to 3) Analog outputs: 0...5 V, 0...10 V, 0...20 mA or 4...20 mA (option)

SiOne transmitters offers Fieldbus (RS-485 – Modbus RTU) or Industrial Ethernet (Modbus TCP) interfaces. The SiOne line can provide up to three fully programmable and scalable Analog outputs (types of output: 0...5 V, 0...10 V, 0...20 mA or 4...20 mA). Analog output can be modified by configurations jumpers, Modbus interface or USB programming unit. SiOne transmitter with relay output can be used as simple binary sensor (pressostat, hygrostat, thermostat, CO2-stat, ...). Threshold and hysteresis of output can be also modified by Modbus or

programming  unit.

## Technical drawing





All dimension in mm. This drawing is for informational purposes only. The manufacturer reserves the right to make changes in the product dimensions without prior notice.

| | |
|---|---|
| **Kod produktu** | Si-U00L1A3 |
| **Typ urządzenia** | Transmitter |
| **Mierzone parametry** | Temperature |
| **Zakres pomiarowy** | -20…+60 °C |
| **Dokładność (maks.)** | ±0.2 °C |
| **Częstotliwość pomiaru** | 1 Hz |
| **Dodatkowe opcje** | – |
| **Typ sensora** | Integrated |
| **Filtr sensora** | Polyethylene filter (40 µm) |
| **Zasilanie** | 11.5…32 VDC / 24 VAC ± 5% (…-HV version), 11.5…27 VDC |
| **Interfejs** | RS-485 (Modbus RTU) |
| **Wyjścia analogowe** | 3x |
| **Wyjścia analogowe - typ** | 0…10 V, 0…20 mA, 0…5 V, 4…20 mA |
| **Wyjścia analogowe - rozdzielczość** | 12-bit |
| **Wyjścia binarne** | – |
| **Wyjścia binarne - parametry** | – |
| **Przyłącze elektryczne** | Screw connection – 16…28 AWG (1,31…0,081 mm²) |
| **Diody serwisowe** | 2x LED |
| **Wyświetlacz** | – |
| **Pamięć - rejestrowane dane** | – |
| **Pamięć - typ** | – |
| **Pamięć - pojemność** | – |
| **Pamięć - częstotliwość zapisu** | – |
| **Parametryzacja** | Configuration software, DIP-switches, Modbus |
| **Stopień ochrony** | IP65 |
| **Temperatura pracy** | -30…+60 °C |
| **Wilgotność pracy** | 0…95 %RH (WITHOUT CONDENSATION) |
| **Typ obudowy** | Duct |
| **Materiał obudowy** | Polycarbonate, Stainless steel |
| **Wymiary obudowy** | See: drawing |
| **W komplecie** | Manual |

## Produkty powiązane


© 2023 APONE apone.eu



Zasilacz ZAS-12-DIN



Kołnierz montażowy KM-15P



XX-XXXXXXX-LOGO



Konwerter CONV-RS485/USB




Konwerter CONV-RS485/LAN



Zasilacz ZAS-24-WT



Puszka przyłączeniowa CONBOX-05



Zasilacz ZAS-24-DIN



Zasilacz ZAS-12-WT


© 2023 APONE apone.eu



Programator CODAP-RS485



Listwa przyłączeniowa CONBLOCK-05

Producent zastrzega sobie prawo do dokonywania zmian niektórych parametrów w związku z ciągłą pracą nad udoskonalaniem konstrukcji urządzenia, bez powiadamiania o tym jego użytkowników.


© 2023 APONE apone.eu